

AMENDMENTS TO THE SPECIFICATION

Please replace the SPECIFICATION, pages 1-7, with the following amended SPECIFICATION:

INJECTION SYRINGE WITH SEAL STRUCTURE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an injection syringe, more particularly, ~~and~~ to an injection syringe with a seal structure which provides a complete seal structure in the injection syringe ~~injection~~.

2. Description of the Related Art

Presently, ~~the~~ many medical personnel are afflicted with ~~suffer the~~ diseases such as AIDS or infection, due to a ~~from the~~ needle stick which can result ~~resulting~~ in death. ~~never stop so that the~~ The needle stick is a common ~~the~~ professional injury and occurs often ~~always happens~~. According to ~~the~~ research, ~~the~~ 98% of medical personnel and 70% of doctors ~~could~~ feel the potential danger of being stuck by a needle ~~and the 70% doctor felt, too~~. Although the injury of needle stick is not serious, ~~but~~ the injury can always lead ~~the~~ to the death of a person ~~to die~~. After using the injection needle with the blood of the patient, the operators could become infected ~~infect~~ if they are stuck ~~hurt~~ by the needle stick.

The needle stick can occur ~~always happens~~ at a patient's bedside or other places ~~the general beds and others~~ such as an operating room, intensive care unit, treatment room and emergency room. ~~What operation is easy to suffer the needle stick, observe the medical behavior?~~ The operation is ~~put the cap back to the needle.~~ Further, the A needle can easily injure ~~is easy to hurt~~ medical personnel when the needle cap is not placed on the needle after use ~~using does not collect~~. Some research is focused to eliminate the operation of placing a ~~putting the~~ cap back on ~~to~~ the needle for avoiding being stuck by the needle ~~stick~~.

Further, the injection syringe of the present invention has ~~some disadvantages~~ many advantages such as the coupling area ~~conjunction connects~~ between the barrel and the axial extension has at least one piercer. Furthermore, ~~The~~ the needle seat is placed in the hollow barrel, and a bottom radius of a body of the needle seat is larger than the top of the body ~~one~~ for tightly fastening with a ~~the~~ seal spring. ~~And~~ Additionally, the top of needle seat has a needle head seat which includes ~~deposits~~ a plurality of positioning sheets ~~at the outside of it~~, and the needle seat is positioned on the axial extension by a channel of the needle head seat.

The top of a plunger ~~plunge~~ has a fastening seat which comprises a cylindrical column. An inclined surface ~~plane~~ of the cylindrical column comprises a plurality of flukes for coupling ~~conjugating~~ to a ~~the~~ bulge loop on the needle seat ~~at the top~~. The top of fastening seat has a piston which includes ~~discloses~~ a hole

for passing the cylindrical column. And, the top of plunger has an opening to couple to the fastening seat and to easily break the plunger after using the syringe.

It is to be understood that both the foregoing general description and the following detailed description are exemplary, and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawing is included to provide a further understanding of the invention, and is incorporated in and constitutes a part of this specification. The drawing illustrates an embodiment of the invention and, together with the description, serves to explain the principles of the invention. In the drawing,

Fig. 1 is an explosive view showing the syringe with seal structure of the present invention;

Fig. 2 is a sectional view showing the syringe with seal structure of the present invention;

Figs. 3 to 10 are schematic diagrams ~~for operation~~ showing operation of the syringe with seal structure of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying

drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

~~Refer~~ Referring to Figs. 1 and 2, the injection syringe of the present invention comprises a hollow barrel 10 which has an axial extension 12 at the top wherein the inside of axial extension 12 comprises an upper channel 14 and a lower channel 16 defining ~~to form~~ a positioning spring 18 and a seal spring 20. The ~~plane point which the conjunction connects~~ of connection between the barrel 10 and extension 12 includes ~~has~~ at least one piercing element ~~piercer~~ 22 projecting inside the barrel 10 ~~at the inside~~. The needle seat 30 is placed in the extension 12 and comprises a body 32. The radius of the bottom of body 32 is larger than the top ~~one~~ of the body 32 for tightly coupling to the seal spring 20. ~~And, the~~ The seal spring 20 has a spring property so that the seal of barrel 10 has an excellent seal property. The bottom of body 32 has a bulge loop 34, and the top of body 32 has a needle head seat 40 which has a needle 42. The outside of needle seat 40 has a plurality of positioning sheets 44, and each seat 44 has a channel 46. When the needle seat 30 is placed in the extension 12, the channel 46 couples to the ~~positional~~ positioning spring 18 for fastening the needle seat 30 in the extension 12. ~~And, each~~ Each positioning sheet 44 at the upper of channel 46 of seat 40 further includes ~~has~~ a pressing channel 48.

A plunger 50 is placed in the barrel 10, and comprises a flange 51 at the bottom. The top of plunger 50 has a fastening seat 52 and an opening 53. The

plunger 50 is coupled ~~conjugated~~ to the fastening seat 52. The fastening seat 52 has an axial channel 54 at the outside and a piston 70. The piston 70 is coupled to the fastening seat 52 by a plurality of fastening channels 56, ~~depositing~~ located on an outside of seat 52, ~~conjugating~~ coupled to a plurality of bulge rings, ~~depositing~~ positioned on an inside of the piston 70. The piston 70 has a hole 74 for passing a cylindrical column 60 of seat 52 and an inclined surface plane at the top. The top of inclined surface plane has a plurality of flukes positioned opposite with respect to each other ~~which opposed to deposit~~, for example: the first fluke 62 is opposite ~~opposes~~ to a second fluke 64 and the first fluke 62 is taller than the second fluke 64.

~~Refer~~ Referring to Figs. 3 to 9, firstly, the needle 42 pierces the ~~sticks the~~ cap of medical bottle and a user pulls the plunger 50 back to draw ~~absorb~~ the medical liquid 80 into the hollow barrel 10. Further, the needle seat 30 must be removed ~~remove~~ from the injection syringe after drawing up ~~absorbing~~ the liquid 80 to allow for a ~~change the~~ new needle seat thereby avoiding a ~~to avoid the rest of~~ cap ~~leaving~~ remaining on the needle 42 when the needle 42 sticks the cap of medical bottle. ~~So, the fingers~~ Therefore a user presses the pressing channel 48 at the upper end of the sheets 44 to remove the needle seat 30 and places ~~put~~ a new needle seat 30 in the extension 12. When the needle seat 30 couples to the extension 12, the channel 46 at the upper end of sheets 22 ~~must~~ is coupled ~~conjugate~~ to the positioning spring 18.

~~Refer~~ Referring to Fig. 4, displacing ~~pushing~~ the plunger 50 towards the extension 12 causes medical liquid 80 to leave ~~toward the up for the air leaving the~~ barrel 10. ~~And,~~ Since the bottom radius of body 32 is larger than the top of the body 32, a tight coupling is formed with the body 32 thereby giving the ~~one to~~ tightly couple to seal spring 20 and ~~for leaving air.~~ Because the barrel 10 has the excellent seal property, ~~the~~ and preventing leakage of medical liquid 80 ~~could not~~ leak.

~~Refer~~ Referring to Fig. 5, displacing ~~pushing~~ the plunger 50 towards the extension 12 causes the medical ~~toward up makes the~~ liquid 80 to be injected ~~inject~~ into the human body.

Refer to Fig. 6, displacing ~~pushing~~ the plunger 50 towards the extension 12 ~~toward up is~~ until the ~~piercer~~ piercing element 22 sticks through the piston 70 causes and makes the flukes 72, 74 62, 64 to couple ~~conjugate~~ with the bulge loop 34. Referring to Fig. 7, the ~~The~~ piston 70 is pierced thereby forming ~~stuck through to form~~ a hole 76, ~~refer to Fig. 7,~~ by the ~~piercer~~ piercing element 22, ~~and the~~ Referring to Fig. 1, the outside wall of fastening seat 52 has the axial channel 54, ~~refer to Fig. 1.~~ The piston 70 has the hole 76 ~~so that~~ which prevents re-use of the barrel 10 is because it is broken ~~because the barrel 10~~ and could will leak to ~~prevent re-use.~~ ~~Refer~~ Referring to Figs. 7 and 8, the flukes 72, 74 ~~conjugates~~ 62, 64 couple with the bulge loop 34~~[[,]]~~ and when the plunger 50 is displaced away from extension 12, such displacement causes the ~~pulls down to make the~~ channel

46 ~~leaving~~ to leave the positioning spring 18 and ~~pull~~ thereby pulls the needle seat 30 into the barrel 10. Further, due to the inclined ~~plane~~ surface and the flukes 62, 64 having different ~~height~~ make heights cause the needle seat ~~aslope~~ to be tilted in the barrel 10 for avoiding reuse of syringe. ~~Refer~~ Referring to Fig. 9, displacing ~~pushing~~ the plunger 50 towards the extension 12 after the needle seat 30 has been pulled into the barrel 10 toward-up makes the deforms needle 42 ~~crankily~~.

~~Refer~~ Referring to Fig. 10, the user spins the plunger 50 to break it and separate ~~to~~ the fastening seat 52.

The injection syringe of the present invention discloses the positioning spring 18 and channel 46 of sheets 44 to ~~make~~ fasten the needle seat 30 ~~fastening~~ on the barrel 10 ~~42~~. Using the seal spring 20 and body 32 ~~get the~~ results in excellent seal property in accordance to the spring property of seal spring 20. The spring 20 ~~could~~ is not ~~be~~ affected by ~~the~~ variations in temperature. Further, after injecting, ~~using the piercer~~ piercing element 22 sticks the piston 70 ~~60~~ to form the hole 76 ~~for losing the seal property~~ to avoid reuse of the syringe by compromising the seal property. Also ~~And~~, spinning the plunger 50 to break and separate ~~to~~ the fastening seat 52 avoids the ability to reuse ~~of~~ the syringe.

Therefore, the foregoing is considered as illustrative only of the principles of the invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation shown and described, and accordingly, all suitable

MR1035-1286

Serial Number: 10/627,653

Reply to Office Action dated 15 November 2005

modifications and equivalents may be resorted to, falling within the scope of the invention.